

# ULT-TPC-PT2441MA-T

## Thermal Network Mini Hybrid Pan & Tilt Camera



- Vanadium oxide uncooled focal plane detector.
- 4Megapixel progressive scan CMOS.
- Powerful 45x optical zoom.
- Supports tripwire, intrusion, and human/vehicle classification.
- Temperature measurement range of  $-20^{\circ}\text{C}$  to  $+550^{\circ}\text{C}$ .
- Pan:  $0^{\circ}$  to  $360^{\circ}$ , tilt:  $-90^{\circ}$  to  $90^{\circ}$ .
- Wide input voltage of 10–36 VDC.
- Maximum IR illumination distance is 100 m.
- IP66 rated.

Featuring thermal and visible channels, Thermal Network Hybrid Pan & Tilt Camera measures temperature through the thermal channel, with high accuracy Max ( $\pm 2^{\circ}\text{C}$ ,  $\pm 2\%$ ), the camera supports multiple temperature measurement rules of spot, line and region at the same time, and generates alarm when the temperature is abnormal, which can help user find potential hazard. The image details can be confirmed by the visible channel. The PTZ with encoder keeps high precision through adjusting in real time. The camera is widely applied in the industrial scenes for temperature measurement of multiple spots.

### Technical Specification

#### Thermal

Detector Type	Vanadium oxide uncooled focal plane detector
Effective Pixels	400 (H) $\times$ 300 (V)
Pixel Pitch	17 $\mu\text{m}$
Spectral Range	8 $\mu\text{m}$ –14 $\mu\text{m}$
Sensitivity (NETD)	$\leq 35 \text{ mK}$ (@f/1.0)
Focal Length	7.5 mm; 13 mm; 25 mm; M25 mm; 50 mm
Field of View	7.5 mm: H: $51.2^{\circ}$ ; V: $38.4^{\circ}$ 13 mm: H: $30.4^{\circ}$ ; V: $22.5^{\circ}$ 25 mm/M25 mm: H: $15.49^{\circ}$ ; V: $11.65^{\circ}$ 50 mm: H: $7.78^{\circ}$ ; V: $5.84^{\circ}$
Thermal Focus Control	7.5 mm: Athermalized 13 mm: Athermalized 25 mm: Athermalized M25 mm: Auto/semi-auto/Manual 50 mm: Athermalized
Close Focus Distance	7.5mm: 0.9 m (2.95 ft) 13 mm: 2.5 m (8.2 ft) 25 mm: 9.2 m (30.18 ft) M25 mm: 0.5 m (1.64 ft) 50 mm: 37 m (121.39 ft)
Digital Detail Enhancement (DDE)	Yes
Thermal Image Stabilization	Electronic Image Stabilization (EIS)
Digital Zoom	19 levels
Thermal AGC	Auto/Manual
Thermal Noise Reduction	2D NR/3D NR

Image Flip	180°
Color Palettes	18 (white hot/black hot/fusion/rainbow/golden autumn/midday/iron red/amber/jade/sunset/icefire/painting/pomegranate/emerald /spring/summer/autumn/winter)
Temperature Measurement Range	Low temperature mode: $-20^{\circ}\text{C}$ to $+150^{\circ}\text{C}$ ( $-4^{\circ}\text{F}$ to $+302^{\circ}\text{F}$ ) High temperature mode: $0^{\circ}\text{C}$ to $+550^{\circ}\text{C}$ ( $+32^{\circ}\text{F}$ to $+1022^{\circ}\text{F}$ ) Auto mode: $-20^{\circ}\text{C}$ to $+550^{\circ}\text{C}$ ( $-4^{\circ}\text{F}$ to $+1022^{\circ}\text{F}$ )
Temperature Measurement Accuracy	Max. ( $\pm 2^{\circ}\text{C}$ , $\pm 2\%$ ); Operating temperature: $-20^{\circ}\text{C}$ ( $-4^{\circ}\text{F}$ ) to $+60^{\circ}\text{C}$ ( $+302^{\circ}\text{F}$ )
Temperature Measurement Mode	Spot: 12 Line: 12 Area: 12 Supports 12 rules simultaneously
Visible	
Image Sensor	1/1.8" CMOS
Max. Resolution	2688 (H) $\times$ 1520 (V)
Pixel	4 MP
Horizontal Definition	Center $\geq 1200$ TVL Edge $\geq 900$ TVL
Min. Illumination	Color: 0.001 lux@F1.4 Black & white: 0.0001 lux@F1.4 0 lux (IR on)
Visible AGC	Auto/Manual
Visible Noise Reduction	2D NR/3D NR
S/N Ratio	>55 dB
White Balance	Auto; manual; indoor; outdoor; tracking; sodium lamp; street lamp; natural
Defog	Optical defog

# UTPC2 Series | ULT-TPC-PT2441MA-T

Image Stabilization	Electronic Image Stabilization (EIS)	Power-off Memory	Yes
Electronic Shutter Speed	1 s–1/30,000 s (auto/manual)	Privacy Masking	4 blocks
BLC	Yes	Idle Motion	Preset; auto pattern; auto tour; pan; progressive scan
WDR	Yes	Function	
HLC	Yes	Two-way Audio	Yes
Day/Night	Auto (ICR); Color; B/W	Network Protocol	HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS; UPnP; NTP; Multicast; SFTP; 802.1x
Iris Control	Auto	Region of Interest (RoI)	Yes
Image Flip	180°	Storage	FTP; Micro SD card (Optional)
Exposure Compensation	Yes	Micro SD Card (Max.)	512 GB
Visible Focus Control	Auto/semi-auto/manual	Interoperability	ONVIF; CGI; ULTTY SDK
Focal Length	5.5 mm–248 mm	Browser	IE: IE8 and later (includes 360 brower and sogou brower) Chrome: 42 and earlier Firefox: 42 and earlier
Field of View	H: 63.5°–1.9° V: 37.4°–1.1°	User/Host	Up to 12 (total bandwidth: 64 MB)
Close Focus Distance	0.5 m–2 m (1.64 ft–6.56 ft)	Security	Authorized username and password; attached MAC address; IEEE 802.1x; controlled network access
Illuminator On/Off Control	Auto/Manual	User Management	Up to 20 users; supports multi-level user permissions (2 levels): management group and user group
Illumination Distance	100 m (328.08 ft, IR) 50 m (164.04 ft, white light)	Malfunction Detection	Network disconnection detection; IP conflict detection; memory card state detection; memory space detection
Audio and Video		PIP	Yes (Intelligence automatically turns off when PIP is on)
Video Compression	H.265; H.264M; H.264H; H.264B	Intelligence	
Resolution	720p main: Main stream: 1280 × 1024; 1280 × 960; 1280 × 720; 400 × 300; 1280 × 960 (default) Sub stream: 640 × 512; 640 × 480; 400 × 300; 400 × 300 (default) Visible: Main stream: 2688 × 1520; 1920 × 1080; 1280 × 720; 704 × 576; 2688 × 1520 (default) Sub stream: 704 × 576; 352 × 288; 352 × 288 (default)	Heat Detection	Yes
	Thermal (50 Hz): Main stream: 1 fps–25 fps, 25 fps by default Sub stream: 1 fps–25 fps, 15 fps by default Visible (50 Hz): Main stream: 1 fps–25 fps, 25 fps by default Sub stream: 1 fps–25 fps, 15 fps by default	Cold/Hot Spot Trace	Yes
Video Frame Rate	Thermal (60 Hz): Main stream: 1 fps–30 fps, 30 fps by default Sub stream: 1 fps–30 fps, 15 fps by default Visible (60 Hz): Main stream: 1 fps–30 fps, 30 fps by default Sub stream: 1 fps–30 fps, 15 fps by default	IVS (Perimeter Protection)	Yes. Supports tripwire and intrusion.
		Target Distinction	Human/Vehicle Classification
PTZ		Port	
Pan/Tilt Range	Pan: 0° to 360° endless Tilt: –90° to +90°	Analog Output	1 × CVBS output; BNC port
Manual Control Speed	Pan: 0.1°/s–100°/s Tilt: 0.1°/s–80°/s	Network Port	1 × RJ-45 (10/100 Base-T)
Preset Speed	Pan: 0.1°/s–100°/s Tilt: 0.1°/s–80°/s	Alarm Input	2
Preset	300	Alarm Output	2
Tour	8 (up to 32 presets per tour)	Audio Input	1
Pattern	5	Audio Output	1
Scan	5	RS-485	1
Power		Power	
Power Supply		Power Supply	Wide input voltage 10–36 VDC
		Power Consumption	Basic: 30 W (illuminator off, heating off) Max: 43 W (illuminator on, heating off); 50 W (illuminator on, heating on)
Environment		Environment	
Operating Temperature	–40 °C to +70 °C (–40 °F to +158 °F)	Operating Temperature	–40 °C to +70 °C (–40 °F to +158 °F)
Operating Humidity	≤95%	Operating Humidity	≤95%

# UTPC2 Series | ULT-TPC-PT2441MA-T

Storage Temperature	-40 °C to +80 °C (-40 °F to +176°F)				
Physical Characteristics					
Protection	IP66				
Reliability	Surge protection: 6 kV Air discharge: 15 kV Contact discharge: 8 kV				
Structure					
Product Dimensions	231.3 mm × 389.7 mm × 276.9 mm (9.11" × 15.34" × 10.9") (L × W × H)				
Packaging Dimensions	485 mm × 360 mm × 390 mm (19.09" × 14.17" × 15.35") (L × W × H)				
Net Weight	≤9 kg (19.84 lb)				
Gross Weight	≤12 kg (26.46 lb)				
Temperature Measurement Distance					
Focal Length	Min. Distance		Max. Distance		
7.5 mm	1 m (3.28 ft)		5 m (16.40 ft)		
13 mm	2 m (6.56 ft)		10 m (32.81 ft)		
25 mm	4 m (13.12 ft)		20 m (65.62 ft)		
M25 mm	4 m (13.12 ft)		21 m (68.90 ft)		
50 mm	9 m (29.53 ft)		45 m (147.64 ft)		
Note: The table displays the measured distances obtained from using the target size 0.1 m × 0.1 m for testing in an environment where the temperature is 23 °C and the relative humidity is below 60%. The table is for reference only. The distances within it are subject to actual conditions including atmospheric conditions, target size, the installation site, and more.					
DRI Distance					
Focal Length	Detection Distance ①	Recognition Distance ②	Identification Distance ③		
7.5 mm	Vehicle: 676 m (2,217.85 ft); Human: 221 m (725.07 ft)	Vehicle: 169 m (554.46 ft); Human: 55 m (180.45 ft)	Vehicle: 85 m (278.87 ft); Human: 28 m (91.86 ft)		
13 mm	Vehicle: 1,173 m (3,848.43 ft); Human: 382 m (1,253.28 ft)	Vehicle: 293 m (961.29 ft); Human: 96 m (314.96 ft)	Vehicle: 147 m (482.28 ft); Human: 48 m (157.48 ft)		
25 mm/M25mm	Vehicle: 2,255 m (7,398.29 ft); Human: 735 m (2,411.42 ft)	Vehicle: 564 m (1,850.39 ft); Human: 184 m (603.67 ft)	Vehicle: 282 m (925.20 ft); Human: 92 m (301.84 ft)		
50 mm	Vehicle: 4,510 m (14,796.59 ft); Human: 1,471 m (4,826.12 ft)	Vehicle: 1,127 m (3,697.51 ft); Human: 368 m (1,207.35 ft)	Vehicle: 564 m (1,850.39 ft); Human: 184 m (603.67 ft)		

① Detection Distance: Detects objects, but cannot recognize their characteristics (objects must cover more than 1.5 pixels of the image).  
 ② Recognition Distance: Classifies objects into general categories, such as human, vehicle (the object must cover more than 6 pixels of the image).  
 ③ Identification Distance: Classifies objects into specific categories based on their characteristics, such as engineering truck, car (the object must cover more than 12 pixels of the image).

#### Note:

The table is the standard theoretical calculation and is for reference only. The distances within it are subject to actual conditions including atmospheric conditions, target size, the installation site, and more. For the intelligent detection distance, refer to the table of Perimeter Protection Distance (IVS Distance) above.

Ordering Information		
Type	Model	Description
Thermal Camera	ULT-TPC-PT2441MA-TB7Z45V1-BC-IR-S22	Thermal: 7.5 mm; Visible: 5.5 mm–248 mm PTZ outlet: side Illuminator type: IR
	ULT-TPC-PT2441MA-TB13Z45V1-BC-IR-S22	Thermal: 13 mm; Visible: 5.5 mm–248 mm PTZ outlet: side Illuminator type: IR
	ULT-TPC-PT2441MA-TB25Z45V1-BC-IR-S22	Thermal: 25 mm; Visible: 5.5 mm–248 mm PTZ outlet: side Illuminator type: IR
	ULT-TPC-PT2441MA-T-BM2 5Z45V1- B C -WB -S22	Thermal: Motorized 25 mm; Visible: 5.5 mm–248 mm PTZ outlet: bottom Illuminator type: white light
	ULT-TPC-PT2441MA-TB50Z45V1-BC-IR-S22	Thermal: 50 mm; Visible: 5.5 mm–248 mm PTZ outlet: side Illuminator type: IR
Accessories (Optional)	R AW021- 0 0	Anti-vibration Isolator

## Accessories

### Optional:



RAW021-00  
Anti-vibration Isolator

Desk Mount	Vehicle Mount

## Dimensions (mm[inch])

